

AT LUX

Solvent-based, stain-proof protective treatment with satin finish effect for natural distressed, brushed or sanded stone.



AT LUX is a solvent-based liquid wax rich in top-quality micro-crystals that are both natural and synthetic, specially developed and formulated to intensify the tone of natural materials, guaranteeing excellent stain- and dirt-proof performance.

AT LUX creates a protective layer that is extremely resistant to foot traffic for stubborn protection against stains and dirt, leaving the treated surface with a warm, satin finish that brings out the full aesthetic characteristics of natural stone.

AT LUX is particularly recommended for use on natural stone with a distressed, brushed or fine sanded finish and can also be used for excellent results on cementina and cement agglomerates. Its use also makes it easier to continue with successive maintenance and cleaning operations, thanks to its high resistance to dirt.

CHARACTERISTICS AND BENEFITS

- ✓ **Brings out the shine and tone** of the material
- ✓ **Effective protection against dirt and staining**
- ✓ Gives the floor excellent **water- and oil-repellent characteristics**
- ✓ Excellent **protection against foot traffic**
- ✓ **Will not yellow**
- ✓ **Applied quickly and easily**
- ✓ **Brings out the full aesthetic qualities of the treated surface**

USES

Product **suitable** for indoor use.

Suitable for use on: Marble-cement agglomerate, Marble-resin agglomerate, Slate, Sandstone, Basaltina - Lava stone, Cementina, Granite, Limestone, Marble, Quartzite, Travertine

COVERAGE

25/35 m²/l

APPLICATION EQUIPMENT

Product application:

Brush, Lambswool applicator, Roller, Cloth

Product polishing:

Mechanical, orbital or flexible floor polisher



Waxes and Finishes

AT LUX Solvent-based, stain-proof protective treatment with satin finish effect for natural distressed, brushed or sanded stone.

APPLICATION STEPS

Preparing and cleaning the surface

1. Carefully clean the surface, making sure to remove any dust or dirt present.
2. Never apply AT LUX to wet or damp surfaces
3. Apply AT LUX to surfaces with a temperature of between +5 and +40°C
4. Any adjacent surfaces not being treated with the product must be protected.

Application

5. Apply an even, abundant coat of product to a clean, dry surface with the preferred tool, making sure to create an even layer to cover the whole surface being treated.

6. Wait about 5-10 minutes and in any case, before the coat of product has dried, then proceed to distribute any product excess on the application area, taking care to even them out until the finished surface is even and homogeneous. When working on small areas, this operation can be carried out with a cloth or white pad. In case of larger surfaces, we recommend using a mechanical polisher, complete with white pad. This operation may not be necessary on particularly absorbent surfaces.

7. 30-60 minutes later but in any case on the completely dry layer of the product, proceed to polish the surface. This operation can be carried out manually on small surfaces, using a wool-cotton cloth, white or wire wool pad. In case of larger areas, we recommend using a tool such as the traditional mechanical polisher (r.p.m. from 150/500) or high-speed mechanical polisher (r.p.m. from 500/1500) or an orbital or flexible polisher, complete with white or lambskin pad, or wire wool or similar. Work the surface, brushing or polishing until all excess has been removed and the end result is both even and polished.

Drying time

The product is fast drying and in any case, no more than 1-2 hours from application.

Opening to floor traffic

The surface can be opened to floor traffic about 4-6 hours after the product has been applied.

COMPLEMENTARY CLEANING AND MAINTENANCE PRODUCTS

- For routine cleaning of a surface treated with AT LUX, we recommend: NEUGEL
- For de-waxing a surface treated with AT LUX, we recommend: DEC 21 and/or DECERA P

INSTRUCTIONS AND GUIDELINES

- Never apply the product to wet or damp surfaces.
- Do not apply the product to overly heated surfaces.
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Do not use on outdoor surfaces.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

EQUIPMENT CLEANING

At the end of application, the equipment used can be cleaned using white spirit.



Waxes and Finishes

AT LUX Solvent-based, stain-proof protective treatment with satin finish effect for natural distressed, brushed or sanded stone.

SAFETY

When applying the product, always use suitable personal protective equipment and carefully follow the instructions on the product safety data sheet.



LINEA
PROFESSIONALE

PHYSICAL AND TECHNICAL INFORMATION

Aspect:	Liquid
Colour:	Matt or transparent (depending on the storage temperature)
Odour:	Solvent
Specific Gravity at 20°C	885 ± 10 g/l
Flash Point (ASTM D 56)	N.A.

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

36 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING

- 1 l bottles - 12 bottles per box
- 5 l cans – 4 cans per box

HAZARD IDENTIFICATION



H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
P210	Keep away from heat/sparks/open flames/hot surfaces. — No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P331	Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P501	Dispose of contents/container to suitable collecting points





Version 2.0 – 17/10/2016

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and / or modify the data and information contained in the data sheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability with regard to the use of such data and suggestions.

FABERSURFACECARE.COM

