

Protective

ATS 60

High-performance, solvent-based, and fast-drying stain-proof treatment for particularly porous and absorbent materials.



ATS 60 is a protective, solvent-based, fast-drying, stain-proof treatment, specifically developed to give top-performance, lasting protection against stains to all materials with a porous structure and therefore, medium-high absorption. **ATS 60** application is fast and simple and does not create superficial film. **ATS 60** is a product that, thanks to its specific formula, is able to slightly enhance the colour of the material on which it is applied, bringing out the veins and the aesthetic features that are characteristic of the surface.

ATS 60 is resistant to UV rays, will not yellow over time and is suitable for use on indoor and outdoor surfaces. **ATS 60** is a product that slightly increases the dirt-resistant properties of the treated surface and can also be used as a surface stain-proof treatment in conjunction with a high penetrant water-repellent primer.

CHARACTERISTICS AND BENEFITS

- ✓ It has pronounced **stain-proof properties**
- ✓ Provides **water-repellency** to the surface
- ✓ Provides **oleo-repellency** to the surface
- ✓ Fast drying
- ✓ **Protects** material **against dirt and staining**
- ✓ Adds a **high degree of water repellence**
- ✓ **Resistant to UV rays**
- ✓ **Will not yellow over time**
- ✓ **Resistant to the elements**
- ✓ **Slightly increases resistance to dirt**

USES

This product **can be used** on both indoor and outdoor surfaces.

Suitable for use on: Cotto, Terracotta, Concrete, Sandstone, Tuff, Quarzites, Porphyry

COVERAGE

10/15 m²/l

APPLICATION EQUIPMENT

Brush, Lambswool applicator, Roller, Cloth



Protective

ATS 60 High-performance, solvent-based, and fast-drying stain-proof treatment for particularly porous and absorbent materials.

APPLICATION STEPS

Preparing and cleaning the surface

1. Carefully clean the surface, making sure to remove any dust or dirt present.
2. Never apply ATS 60 to wet or damp surfaces.
4. Apply ATS 60 to surfaces with a temperature of between +5 and +40°C
5. Any adjacent surfaces not being treated with the product must be protected.

Application

6. Apply an even, thin coat of product to a clean, dry surface with the preferred tool, making sure to create an even layer to cover the whole surface being treated
7. The product is fast drying and usually does not create residues. When applied to a compact surface that is not very absorbent, it could leave slight residues on the surface that can be easily wiped off with a clean, dry cloth. In case of very absorbent surfaces, we recommend applying a second coat of product, no less than 45 minutes after the first.

Drying time

The product is fast drying and in any case, within 45 minutes from application.

Opening to floor traffic

The surface can be opened to floor traffic about 2-3 hours after the product has been applied.

COMPLEMENTARY CLEANING AND MAINTENANCE PRODUCTS

- For *routine cleaning* of a surface treated with ATS 60, we recommend: NEUGEL or ALGAFLOOR
- For *extraordinary cleaning* of a surface treated with ATS 60, we recommend: FABER 30 or DETERFUG, according to the type of stone to be cleaned
- For *de-waxing* a surface treated with AS 930, we recommend: DEC 21 and/or DECERA P

INSTRUCTIONS AND GUIDELINES

- Never apply the product to wet or damp surfaces.
- If the product is applied as a stain-proof treatment on a material that has already been primed with a high penetrant water-repellent, wait for this to dry completely before applying ATS 60
- Do not apply the product to overly heated surfaces.
- Do not apply the product when there is an imminent risk of rain or frost, or in presence of mist, fog or high levels of humidity.
- Apply the product to surfaces with a temperature of between +5 and +35°C
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

EQUIPMENT CLEANING

At the end of application, the equipment used can be cleaned using white spirit.

SAFETY

When applying the product, always use suitable personal protective equipment and follow the instructions on the product safety data sheet with care.



FABERSURFACECARE.COM



Protective

ATS 60 High-performance, solvent-based, and fast-drying stain-proof treatment for particularly porous and absorbent materials.

PHYSICAL AND TECHNICAL INFORMATION

Aspect	: Liquid
Color	: Transparent
Odour	: Solvent acetate
Specific gravity (20°C)	: 905 ± 15 g/lt.
Flash point (ASTM D 56)	: 23°C open vase

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

24 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING

- 1 l bottles - 12 bottles per box
- 5 l cans – 4 cans per box

HAZARD IDENTIFICATION



H226	Flammable liquid and vapours.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure can cause skin dryness or crackings.
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of the reach of children
P210	Keep away from heat/ hot surfaces/ sparkles / free flames / hot surfaces. No smoking.
P233	Keep container tightly closed.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.

Version 2.1 – 11/10/2017

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and / or modify the data and information contained in the data sheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability with regard to the use of such data and suggestions.

