

B1 920

Easy-application, water-based wax polish for vertical surfaces or areas not subject to foot traffic



B1-920 is a wax-resin emulsion developed to replace solid or solvent-based liquid wax, especially for vertical surfaces or surfaces not subject to foot traffic.

B1-920 creates a fine, ultra-resistant film that boosts surface shine, bringing out the full colour and aesthetic appearance while at the same time, making treated materials easier to clean.

B1-920 has been specifically developed for all surfaces not subject to foot traffic, where it would be complicated to proceed with polishing using traditional methods, such as vertical surfaces or bathroom tops, stone work tops and also to replace more traditional products with strong, pungent odours due to the presence of strong solvents.

CHARACTERISTICS AND BENEFITS

- ✓ **Brings out the shine** on treated materials
- ✓ **Increases surface hardness of the support**
- ✓ **Makes the subsequent daily cleaning operations much simpler**
- ✓ **Quick and easy application**
- ✓ **Can also be used on surfaces treated with other waxes**
- ✓ **Ideal for polishing walls, vertical surfaces or horizontal surfaces not subjected to foot traffic**

USES

Product **suitable** for indoor use.

Suitable for use on: Granite, Marble, Limestone, Travertine

COVERAGE

20/30 m²/l for first-time application.
30/50 m²/l for maintenance.

APPLICATION EQUIPMENT

Product application:

Brush, Lambswool applicator, Roller, Cloth, Spray

Product polishing

Mechanical, orbital or flexible polisher



Waxes and Finishes

B1 920 Easy-application, water-based wax polish for vertical surfaces or areas not subject to foot traffic



APPLICATION STEPS

Preparing and cleaning the surface

1. Carefully clean the surface, making sure to remove any dust or dirt present.
2. Never apply B1 920 to wet or damp surfaces.
3. Apply B1 920 to surfaces with a temperature of between +5 and +40°C
4. Any adjacent surfaces not being treated with the product must be protected.
5. We recommend working on small areas in order to polish them easily with the orbital or flexible polisher.
6. Before proceeding with to apply the product, we recommend pouring B1 920 into a spray applicator bottle with a wide nozzle. This serves to apply the product to the surface, notably speeding up the work process.

Application

7. Shake the bottle thoroughly and spray a small amount of product directly onto the area to be treated. Generally, about 2-3 sprays of product are enough for treating small sections of an area.

8. As soon as the product has been applied, proceed to polish the surface. This operation can be carried out manually on small surfaces, using a wool-cotton cloth, white or wire wool pad. In case of larger areas, we recommend using a tool such as the orbital or flexible polisher, complete with white or lambskin pad, or wire wool or similar.

Pass the polisher being sure to use concentric movements so as to distribute the product evenly over the whole section being treated.

9. Work the surface, brushing or polishing until all excess has been removed (*Spray Buffing technique*) and the end result is both even and polished.

10. Pass on to the next section, repeating the polishing treatment process as described above.

11. After treating all of the surface areas, remove any steel wool residues from the surface using a dry cloth (*Dry mop*)

Drying time

After the product is completely dry, no further waiting time is necessary.

Opening to floor traffic

The product is not for use on areas subject to foot traffic.

COMPLEMENTARY CLEANING AND MAINTENANCE PRODUCTS

- For de-waxing a surface treated with B1 920, we recommend: DEC 21 and/or DECERA P



FABERSURFACECARE.COM



Waxes and Finishes

B1 920 Easy-application, water-based wax polish for vertical surfaces or areas not subject to foot traffic



INSTRUCTIONS AND GUIDELINES

- Never apply the product to wet or damp surfaces.
 - Do not apply the product to overly heated surfaces.
 - When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
 - Do not use on outdoor surfaces.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

EQUIPMENT CLEANING

At the end of application, the equipment used can be washed using water.

SAFETY

When applying the product, always use suitable personal protective equipment and carefully follow the instructions on the product safety data sheet.

PHYSICAL-TECHNICAL DATA

Aspect:	Liquid
Colour:	White
Odour:	Sweet
pH	9 ± 0.5
Specific Gravity at 20°C	1000 ± 5 g/l

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

36 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING

- 1 l bottles - 12 bottles per box
- 5 l cans – 4 cans per box

HAZARD IDENTIFICATION

This product is not subject to classification according to current standards.

Version 3.0 – 17/10/2016

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and / or modify the data and information contained in the data sheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability with regard to the use of such data and suggestions.

