

SO 9001



Protective

CP 5

Maintenance treatment with scratch-proof properties for surfaces treated with acid-proof treatment AS 930 CP



CP 5 is a water-based ready to use product to be used for the maintenance of surfaces previously treated with the acid-proof treatment AS 930 CP. The product increases the scratch resistance of the surface and increases the lasting and effectiveness of the acid-proof properties.

CHARACTERISTICS AND BENEFITS

- Increases the lasting of AS 930 CP acid-proof properties
- Increases the scratch-resistance of the surface

USES

This product can be used on both indoor and outdoor surfaces. Suitable for use on all the surfaces previously treated with AS 930 CP

COVERAGE

40/50 m²/l

APPLICATION EQUIPMENT

Micro-fiber cloth; non-woven fabric

APPLICATION STEPS

Spray the product on the surface and distribute omogeneously and evenly by using a non-woven fabric cloth or a micro-fiber cloth. Wait the complete drying of CP 5. After the drying remove the residues and re-polish the surface simply using the same cloth used for the application. Before Apply CP 5 on the surface, wait for the complete drying of the treatment AS 930 CP previously applied.

INSTRUCTIONS AND GUIDELINES

- Never apply the product to wet, damp or dirty
- Do not apply the product to overly heated surfaces.
- After applying a layer of AS 930 CP, let it curing without re-touching or intervening in the treated area before it is completely dry; this is to prevent uneven finishes after drying.
- Avoid to use blades directly on the surface, using instead a proper cutting board

EQUIPMENT CLEANING

At the end of application, the equipment used can be cleaned using water.

SAFETY

When applying the product, always use suitable personal protective equipment and follow the instructions on the product safety data sheet with care.







Protective

CP 5 Maintenance treatment with scratch-proof properties for surfaces treated with acid-proof treatment AS 930 CP



PHYSICAL AND TECHNICAL INFORMATION	
Aspect	: Liquid
Color	: Opalescent
Odour	: Typical

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

12 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING

- 1 Lt bottles - 12 bottles per box











Version 0.0 – 02/12/2019

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and / or modify the data and information contained in the data sheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability with regard to the use of such data and suggestions.

