NO OIL

Product to remove deep penetrating oil stains, grease and greasy residues.



NO OIL is a solvent-based stain remover to be used to extract and remove grease stains from all types of surface

With its special formulation, the product can offer effective, definitive action on:

- Stains from food oil and greasy foods;
- Stains from mineral oil, engine oil, diesel and lubricants
- Greasy stains and bituminous residues

NO OIL is a product that can be applied on all surfaces - even the most delicate types such as polished marbles and acid-sensitive finishes - without attacking them or causing them to lose their shine.

The special thick, creamy formula of **NO OIL** boosts its stain-extracting action, guaranteeing improved efficiency in terms of stain removal. It is also easy to use and effective on vertical surfaces.

Once applied over the stain to be removed, the product works alone without needing any further processes, until it completely removes the stain. **NO OIL** is quick and easy to apply, and its use will not alter the surface's original appearance.

CHARACTERISTICS AND BENEFITS

- ✓ High stain extraction capacity
- Quick and easy application
- ✓ Will not ruin treated surfaces
- Also suitable for vertical surfaces

USES

This product can be used on both indoor and outdoor surfaces.

Suitable for use on: Marble-resin agglomerate, Quartz-resin agglomerate, Slate, Sandstone, Basaltina - Lava stone, Molten basalt, Cementina, Concrete, Craquelé ceramics, Glazed ceramics, Clinker, Cotto, Granite, Lapped porcelain stoneware, Polished porcelain stoneware, Natural porcelain stoneware, Textured porcelain stoneware, Cement grout, Limestone, Marble, Exposed brick, Reconstituted stone (Eco stone), Porphyry, Quarzite, Terracotta, Travertine, Tuff

COVERAGE

N.A.

APPLICATION EQUIPMENT

Brush, Spatula, Direct application to stains



SO 900













NO OIL - Product to remove deep penetrating oil stains, grease and greasy residues.

APPLICATION STEPS

Preparing and cleaning the surface

- 1. Carefully clean the surface, making sure to remove any dust or dirt present.
- 2. Never use NO OIL on wet surfaces; make sure that the surface to be treated is dry or at most, only slightly damp.
- 3. Do not apply NO OIL to overly heated surfaces. We recommend applying the product during the coolest periods of the day.
- 4. In the case in which the surface to be treated has a previous surface layer of wax, proceed to the removal of the same with Double Stripping.

Application

NO OIL must only be used alone. NEVER mix it with other chemicals.

- 5. Shake well before use. The product is for use without dilution. Pour the product straight onto the surface being treated. Use a brush, spatula or if simpler, pour directly onto the surface, covering it completely with a thick layer of product.
- 6. Leave the product to act on the surface until it is completely dry. The product will become a white powdery residue as it dries. It is fast drying and in any case, no more than 1-2 hours from application.
- 7. Once the product is completely dry, proceed to remove the powder residue using a soft bristled broom or clean brush if treating porous material; for compact, non-absorbent materials, the residue can be removed with absorbent paper, a towel or a cloth. Once all powder residues have been removed, wipe the surface with a slightly damp cloth or mop and wait for it to dry thoroughly before assessing the stain removal results.

If the finished result is not totally satisfactory, repeat the product application process as described above. If the stain is mixed in origin, it may be a good idea also to use another type of stain remover.

When treating particularly porous surfaces, such as sandstone or handmade cotto, after stain removal, it may be necessary to remove any remaining powder trapped in the pores. To do this it is possible to use a vacuum cleaner or liquid cleaner, and an extractive detergent, Deterfuq. In more difficult cases, it is possible to use a pressurised washer.

Opening to floor traffic

8. After rinsing the surface with water, wait for the floor to dry completely before opening to foot traffic.

COMPLEMENTARY CLEANING AND MAINTENANCE PRODUCTS

- For routine cleaning of a surface treated with NO OIL we recommend: NEUGEL or ALGAFLOOR
- For extraordinary cleaning of a surface treated with NO OIL we recommend: FABER 30 or DETERFUG, according to the type of surface to be cleaned
- Following a stain removal operation using NO OIL we recommend using a damp-proofing and/or stain-proofing treatment to be selected according to the characteristics and intended use of the surface.



Stain removers

NO OIL - Product to remove deep penetrating oil stains, grease and greasy residues.



INSTRUCTIONS AND GUIDELINES

NO OIL must only be used alone. NEVER mix it with other chemicals, except for Faber Poultice thickening powder

- Do not apply the product to overly heated surfaces.
- Do not apply the product when there is an imminent risk of rain or frost, or in the presence of mist.
- While applying the product to the surface concerned it must not be exposed to direct sunlight.
- Apply the product to surfaces in temperatures of between +5 and +40°C
- When using on recently laid or grouted surfaces, wait for the grout to cure completely.
- To achieve a visually pleasing, even result, above all in case of absorbent surfaces, we recommend applying the stain remover by treating areas that are larger than the single stained portions, such as a whole tile or room. These area can be decided according to the size and spread of the stain.
- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.

EQUIPMENT CLEANING

At the end of application, the equipment used can be washed using water.

SAFETY

When applying the product, always use suitable personal protective equipment and carefully follow the instructions on the product safety data sheet.

PHYSICAL AND TECHNICAL INFORMATION	
Aspect:	Gel
Colour:	White
Odour:	Solvent
Specific gravity at 20°C:	1065 ± 20 g/l
Flash point (ASTM D 56)	21°C

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

24 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING

- 0.5 I bottles - 12 bottles per box













NO OIL - Product to remove deep penetrating oil stains, grease and greasy residues.



HAZARD IDENTIFICATION



•	
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer .
EUH066	Repeated exposure may cause skin dryness or cracking.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition
	sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin
	with water/shower
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Version 3.0 - 24/03/2017

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and / or modify the data and information contained in the data sheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability with regard to the use of such data and suggestions.











