

Cleaner

SCRATCH OFF CLEANER

Degreaser alkaline cleaner for surface cleaning
before restoration with FABER SCRATCH OFF technology



LINEA
PROFESSIONALE

SCRATCH OFF CLEANER is a concentrated alkaline-based cleaner that is extremely effective when it comes to deep-down cleaning of all surfaces with general dirt - including long standing - caused through a normal build up on floors from normal usage

SCRATCH OFF CLEANER is a versatile cleaner that is quick and easy to use, while being strong on dirt but at the same time, extremely gentle on surfaces, even the most delicate types. This is why it can be used on surfaces of all types, including polished or glazed polished porcelain tiles and ceramic slabs.

SCRATCH OFF CLEANER can be used even on floors with high foot traffic, since it is very effective against foot-traffic dirt, also thank to its deep-extractive action.

SCRATCH OFF CLEANER removes dirt and soils, preparing the surface to the use of **FABER SCRATCH OFF** technology to restore scratches, defects, dulness and abrasions.

FEATURES AND BENEFITS

- ✓ Effective against different kind of dirt
- ✓ Ideal solution to remove foot-traffic dirt
- ✓ Delicate on surface but strong against dirt
- ✓ Suitable to remove greasy dirt on kitchen or bathroom countertops

APPLICATION FIELDS

Suitable for: outdoor or indoor application

Suitable for: polished porcelain ceramic tile (full body polished or glazed polished)

CONSUMPTION

10-15 m²/l

APPLICATION TOOLS

Cloth, Sponge, White Pad

FABERSURFACECARE.COM



Cleaner

SCRATCH OFF CLEANER

*Degreaser alkaline cleaner for surface cleaning
before restoration with FABER SCRATCH OFF technology*



APPLICATION STEPS

Preparing and cleaning the surface

1. Before proceeding to wash the surface with SCRATCH OFF CLEANER, it is advisable to clean away any surface residues, such as dust, debris and coarse dirt, using a broom or a vacuum cleaner,

Application

2. The product can be used undiluted or it can be diluted in clean water, according to the amount of dirt that needs to be removed:

- If used as strong degreasing cleaner to remove foot-traffic dirt, stubborn and aged dirt the product should be diluted to 20-30% in water (1 part of product in 2/4 parts of water)
- If used as simple cleaning products to clean a ceramic slab before the restoration the product should be diluted to 10% in water (1 part of product in 9 parts of water)

Before apply the product on the whole surface make a preliminary test on a small portion of the surface.

3. Apply the product in the selected dilution ratio to the surface, covering the whole area being cleaned and distributing it evenly and vigorously with a white pad.

4. Leave the product to work for about 10-15 minutes, helping its dissolving action by passing over with white pad at more or less regular time intervals, according to the difficulty in removing the residues that need to be dissolved. This will boost the dissolving action of the product and give you better results.

5. Remove the residues and rinse well with clean water. If the result is not completely satisfying, repeat the operation, following the steps above. After the preliminary test, if the surface shows resistance, the product can be used pure and with longer contact times.

INSTRUCTIONS AND GUIDELINES

- Before applying the product to the whole surface, it is advisable to test a small, unexposed area or unused piece to check its suitability for use.
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely
- Do not mix with other chemical compounds
- If the finished result is not totally satisfactory, repeat the process as described above.

EQUIPMENT CLEANING

At the end of application, the equipment used can be washed using water.



Cleaner

SCRATCH OFF CLEANER

Degreaser alkaline cleaner for surface cleaning
before restoration with FABER SCRATCH OFF technology



LINEA
PROFESSIONALE

SAFETY

When applying the product, always use suitable personal protective equipment and follow the instructions on the product safety data sheet with care.

PHYSICAL AND TECHNICAL INFORMATION

Aspect:	Liquid
Colour:	Amber
Odour:	Typical
pH:	12,5 ± 0,5
Specific Gravity at 20°C	1050± 10 g/l

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

36 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING

- 0,5 liter bottle



HAZARD IDENTIFICATION

H314	Causes severe skin burns and eye damage.
P234	Keep only in original container.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P310	Immediately call a POISON CENTER or doctor/physician.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P390	Absorb spillage to prevent material damage.
P406	Store in corrosive resistant/... container with a resistant inner liner.

FABERSURFACECARE.COM

Revision 0.0 – 15/03/2018

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and / or modify the data and information contained in the data sheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability with regard to the use of such data and suggestions.



SCRATCH OFF LIGHT

Professional treatment to restore scratches, abrasions, dullness and defects from light coloured polished porcelain ceramic tiles



SCRATCH OFF LIGHT is an innovative liquid product specifically developed to definitely restore scratches, defects, abrasions and dullness from the surfaces made of light coloured polished porcelain ceramic tiles, restoring in a fast and simple way the original look of the treated surface.

SCRATCH OFF LIGHT should be applied by using professional hand-tools like polisher, equipped with the specific FabK pad. The product can be easily applied on vertical or horizontal surfaces. The product can be used also on already installed tiles/slabs, and so it can be used on tables, kitchen or bathroom countertops, furnitures and every other design element made of porcelain ceramic tiles. The product is suitable also for use on floors.

SCRATCH OFF LIGHT is a ready to use product and the application does not require water. For this reason it could be easily used even on already installed surfaces as it creates a very low dusty residues that can be easily rinsed away with water at the end of the restoration procedure.

FEATURES AND BENEFITS

- ✓ **Definitive restoration of scratches, defects, dullness and abrasions**
- ✓ **Application by hand-polisher: easy use on vertical or horizontal surfaces**
- ✓ **It can be use before or after the installation of the ceramic slab/tile**
- ✓ **Fast and easy application**
- ✓ **The use does not create heavy residues**
- ✓ **The use does not require water**

CAMPI D'IMPIEGO

Suitable for: outdoor or indoor application

Suitable for: light coloured polished porcelain ceramic tile (full body polished or glazed polished)

CONSUMPTION

Product consumption may change depending on depth and wide of scratch/defects to be restored

APPLICATION TOOL

Polymer hand-tool equipped with FabK pad, provided inside the Kit



SCRATCH OFF LIGHT

Professional treatment to restore scratches, abrasions, dulness and defects from light coloured polished porcelain ceramic tiles



APPLICATION STEPS

Preparing and cleaning the surface

1. Carefully clean the surface removing dust and dirt
2. If the surface is dirt, use the specific cleaner SCRATCH OFF CLEANER (see product Technical Data Sheet)
3. Rinse well the surface with water and dry with cloth or absorbent paper
4. Before apply the product we suggest to delimit and mask with plastic sheet the area of the surface that need to be restored

Application

5. Shake very well the bottle and apply, directly on the surface that need to be restored, some drops of product until the scratch/defect is covered by the product.

6. Without turning on the polisher, distribute the product on the surface by using the FAB K Pad

7. Turn on the polisher and start brushing the product on the surface with linear movements that follows the direction of the scratch. Do not apply too much pressure on the tools: in this phase is sufficient to follow the movement of the tools, taking care of working by using all the flat surface of the FAB K pad. Is enough to work just on the scratched area.

8. Proceed with the brushing of the surface until the product is completely dry on the surface. If on the adjacent surface are visible some product residues, those will be easily removed once the application is over. It is important to brush only in the scratched area.

9. When the product is completely dry on the surface evaluate the obtained result. If the scratch should be still visible, repeat the application by following the same instructions. The number of applications necessary to have a full restoration depends from the depth and width of the scratch. Generally, as an indication, 3-5 applications are enough to have a satisfactory result, however for deeper or wider scratches it is possible to make all the application necessary for a full restoration.

10. Once the desired result is obtained rinse well with clean water and rub the surface with WITE PAD to remove product residues and splashes. In the end wipe the surface with a paper towel or a cloth. If on the surface should be still visible some stubborn residues of product, buff them with a dry FAB K pad, without using any product.



SCRATCH OFF LIGHT

Professional treatment to restore scratches, abrasions, dulness and defects from light coloured polished porcelain ceramic tiles



INSTRUCTIONS AND GUIDELINES

- Shake very well the bottle before use
- Proceed with the application one scratch at time
- Do not work on large areas
- Do not apply too much pression on the hand-tool
- Do not apply on wet surface
- Do not apply on over-heated surface
- Before apply the product on the whole surface, always make a preliminary test to evaluate the final result.

EQUIPMENT CLEANING

At the end of application, the equipment used can be washed using water.

SAFETY

When applying the product, always use suitable personal protective equipment and follow the instructions on the product safety data sheet with care.

PHYSICAL AND TECHNICAL INFORMATIONS

Aspect:	Opalescent liquid
Colour:	White
Odour:	Odourless
pH:	8,5 ± 0,5
Specific Gravity at 20°C	1316 ± 10 g/l

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

48 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING

- 250 ml bottle

HAZARD IDENTIFICATION

NOT SUBJECTED

Revision 0.0 – 15/03/2018

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and / or modify the data and information contained in the data sheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability with regard to the use of such data and suggestions.



SCRATCH OFF DARK

Professional treatment to restore scratches, abrasions, dullness and defects from dark coloured polished porcelain ceramic tiles



SCRATCH OFF DARK is an innovative liquid product specifically developed to definitely restore scratches, defects, abrasions and dullness from the surfaces made of dark coloured polished porcelain ceramic tiles, restoring in a fast and simple way the original look of the treated surface.

SCRATCH OFF DARK should be applied by using professional hand-tools like polisher, equipped with the specific FabK pad. The product can be easily applied on vertical or horizontal surfaces. The product can be used also on already installed tiles/slabs, and so it can be used on tables, kitchen or bathroom countertops, furnitures and every other design element made of porcelain ceramic tiles. The product is suitable also for use on floors.

SCRATCH OFF DARK is a ready to use product and the application does not require water. For this reason it could be easily used even on already installed surfaces as it creates a very low dusty residues that can be easily rinsed away with water at the end of the restoration procedure.

FEATURES AND BENEFITS

- ✓ **Definitive restoration of scratches, defects, dullness and abrasions**
- ✓ **Application by hand-polisher: easy use on vertical or horizontal surfaces**
- ✓ **It can be use before or after the installation of the ceramic slab/tile**
- ✓ **Fast and easy application**
- ✓ **The use does not create heavy residues**
- ✓ **The use does not require water**

CAMPI D'IMPIEGO

Suitable for: outdoor or indoor application

Suitable for: dark coloured polished porcelain ceramic tile (full body polished or glazed polished)

CONSUMPTION

Product consumption may change depending on depth and wide of scratch/defects to be restored

APPLICATION TOOL

Polymer hand-tool equipped with FabK pad, provided inside the Kit



SCRATCH OFF DARK

Professional treatment to restore scratches, abrasions, dulness and defects from dark coloured polished porcelain ceramic tiles



APPLICATION STEPS

Preparing and cleaning the surface

1. Carefully clean the surface removing dust and dirt
2. If the surface is dirt, use the specific cleaner SCRATCH OFF CLEANER (see product Technical Data Sheet)
3. Rinse well the surface with water and dry with cloth or absorbent paper
4. Before apply the product we suggest to delimit and mask with plastic sheet the area of the surface that need to be restored

Application

5. Shake very well the bottle and apply, directly on the surface that need to be restored, some drops of product until the scratch/defect is covered by the product.

6. Without turning on the polisher, distribute the product on the surface by using the FAB K Pad

7. Turn on the polisher and start brushing the product on the surface with linear movements that follows the direction of the scratch. Do not apply too much pressure on the tools: in this phase is sufficient to follow the movement of the tools, taking care of working by using all the flat surface of the FAB K pad. Is enough to work just on the scratched area.

8. Proceed with the brushing of the surface until the product is completely dry on the surface. If on the adjacent surface are visible some product residues, those will be easily removed once the application is over. It is important to brush only in the scratched area.

9. When the product is completely dry on the surface evaluate the obtained result. If the scratch should be still visible, repeat the application by following the same instructions. The number of applications necessary to have a full restoration depends from the depth and width of the scratch. Generally, as an indication, 3-5 applications are enough to have a satisfactory result, however for deeper or wider scratches it is possible to make all the application necessary for a full restoration.

10. Once the desired result is obtained rinse well with clean water and rub the surface with WITE PAD to remove product residues and splashes. In the end wipe the surface with a paper towel or a cloth. If on the surface should be still visible some stubborn residues of product, buff them with a dry FAB K pad, without using any product.



SCRATCH OFF DARK

Professional treatment to restore scratches, abrasions, dulness and defects from dark coloured polished porcelain ceramic tiles



INSTRUCTIONS AND GUIDELINES

- Shake very well the bottle before use
- Proceed with the application one scratch at time
- Do not work on large areas
- Do not apply too much pression on the hand-tool
- Do not apply on wet surface
- Do not apply on over-heated surface
- Before apply the product on the whole surface, always make a preliminary test to evaluate the final result.

EQUIPMENT CLEANING

At the end of application, the equipment used can be washed using water.

SAFETY

When applying the product, always use suitable personal protective equipment and follow the instructions on the product safety data sheet with care.

PHYSICAL AND TECHNICAL INFORMATIONS

Aspect:	Liquid
Colour:	Black
Odour:	Odourless
pH:	10.0 ± 0,4
Specific Gravity at 20°C	1320 ± 10 g/l

STORAGE

Keep the container tightly closed and store in a cool, dry place.

SHELF LIFE

48 months in the original, sealed packaging, stored in a cool, dry place.

PACKAGING

- 250 ml bottle

HAZARD IDENTIFICATION

NOT SUBJECTED

Revision 0.0 – 15/03/2018

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and / or modify the data and information contained in the data sheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability with regard to the use of such data and suggestions.

